● PRINTER RUSH ●
(PTO ASSISTANCE)

Application : 09/552292 **Examiner :** Kiss **GAU :** 2192

From: MWD **Location:** (IDC) FMF FDC **Date:** 11/18/05

Tracking #: EDM-09/552292 Week Date: 9/26/05

DOC CODE	DOC DATE	MISCELLANEOUS
☐ 1449		☐ Continuing Data
☐ IDS		☐ Foreign Priority
☐ CLM		☐ Document Legibility
☐ IIFW		☐ Fees
☐ SRFW		☐ Other
☑ DRW	4-19-00	
☐ OATH		
☐ 312		
☐ SPEC		

[RUSH] **MESSAGE:** ATTN: Chief Draftsperson

① Fig. 20 is cut off on the right side. If possible, please provide a complete replacement for this drawing.

Thanks

[XRUSH] **RESPONSE:**

Drwgs corrected

INITIALS: JJS

NOTE: This form will be included as part of the official USPTO record, with the Response document coded as XRUSH.

REV 10/04

FIG. 1


100
struct S {
S() throw(); 101
~S() throw(); 102
};
103
struct T {
T(); 104
~T(); 105
};
void woof(); 106
...
L1: {
T ant; 107
108 try { 109
if(x>0) {
S boa; 110
111 } else {
S cat; 112
T dog; 113
woof(); 114
115 }
116 } catch(int y) { 117
S elk; 118
woof(); 119
120 }
} 121
L2:;


#include <setjmp.h>
200
struct EH_item {
201
struct EH_item * next;
enum {DESTROY,TRY} tag;
202
union {
struct {
void * object;
203
void (*dtor)();
204
} destructor;
struct {
jmp_buf buffer;
205
struct handler_spec* handlers;
206
} try_block;
};
};
struct EH_item * EH_stack_ptr;
207

FIG. 2



```
        struct EH_item ra, rb, rc, rd, re, rt;
        L1:
303     T(&ant);
304     ra.kind = DESTROY;
        ra.destructor.object  = &ant; ra.destructor.dtor = &~T;
306     ra.next = EH_stack_ptr;  EH_stack_ptr = &ra;
307     rt.kind = TRY;
        rt.next = EH_stack_ptr;
        rt.try_block.handlers = ...;
31      rt.next = EH_stack_ptr;  EH_stack_ptr = &rt;
31      if( setjmp( rt.try_block.buffer)==0 ) {
            if( x>0 ) {
        313 S(&boa);
        314 rb.kind = DESTROY;
                rb.destructor.object  = &boa; rb.destructor.dtor = &~S;
                rb.next = EH_stack_ptr;  EH_stack_ptr = &rb;
        31      EH_stack_ptr = EH_stack_ptr->next;
                ~S(& boa);
            } else {
                S(cat);
                rc.kind = DESTROY;
                rc.destructor.object  = &cat; rc.destructor.dtor = &~S;
                rc.next = EH_stack_ptr;   EH_stack_ptr = &rc;
                T(&dog);
                rd.kind = DESTROY;
                rd.destructor.object  = &dog; rd.destructor.dtor = & ~T;
                rd.next = EH_stack_ptr;   EH_stack_ptr = &rd;
                woof();
                EH_stack_ptr = EH_stack_ptr->next;
                ~T(&dog);
                EH_stack_ptr = EH_stack_ptr->next;
                ~S(& cat);
            }
        } else {
            S(&elk);
            re.kind = DESTROY;
            re.destructor.object  = &elk; re.destructor.dtor = address of ~S();
            re.next = EH_stack_ptr;  EH_stack_ptr = &re;
            ~S(&elk);
            EH_stack_ptr = EH_stack_ptr->next;
        }
342     EH_stack_ptr = EH_stack_ptr->next;
343     EH_stack_ptr = EH_stack_ptr->next;
34      ~T(ant);
        L2:
```

FIG. 3
PRIOR ART


start
400
Determine state of target data structure at selected program points
401
Partition state of target data structure into components
402
Determine operations to be inserted at each selected program point in order to set each component of the state at that program point.
403
Compute placement of setting operations that eliminates partial redundancies
404
Place the setting operations in the program according to the computed placement.
end

FIG. 4


502
(succeed)
501
T(&ant)
L1
500
(fail)
x>0?
503
(true)
(false)
504
507
S(&cat)
508
T(&dog)
509
(fail)
(succeed)
510
S(&boa)
woof()
511
(fail)
515
(succeed)
512
~T(&dog)
513
(fail)
(succeed)
514
505
~S(&cat)
~S(&boa)
~S(&elk)
506
522
~T(&ant)
L2
(succeed)
(fail)
527
526
525
match int?
517
~ S(&cat)
518
(true)
(false)
516
~T(&dog)
519
S(&elk)
520
woof()
521
(succeed)
(fail)
~S(&elk)
523
524
~T(&ant)

FIG. 5


start
600
Does routine have cleanup instructions?
no
yes
601
Build cleanup tree and cleanup states for routine.
602
Compute down-safety transfer function DOWNSAFE(e) for each edge.
604
Compute up-safety transfer function UPSAFE(e).
Solve flow-equations for DOWNSAFE*.
603
Solve flow equations for UPSAFE*.
605
Use DOWNSAFE* and UPSAFE* to place instructions that set components of the exception-handling stack.
606
Remove exceptional edges
607
Insert prologue
608
end

FIG. 6


701
(succeed)
T(&ant)
L1
700
x>0?
(true)
(false)
~S(&cat)
try
~T(&ant)
S(&cat)
708
T(&dog)
709
(succeed)
~T(&dog)
~S(&cat)
try
~T(&ant)
710
woof()
711
(succeed)
712
~S(&cat)
try
~T(&ant)
~T(&dog)
713
(succeed)
S(&elk)
~S(&elk)
~T(&ant)
720
woof()
721
(succeed)
~S(&boa)
~S(&cat)
~S(&elk)
706
~T(&ant)
(succeed)
726

FIG. 7



FIG. 8


start CLEANUP_TREE(u)
900
Has STATE[u] been set yet?
yes
Allocate a new cleanup node n
Set PARENT[n] := nil
ROOT:=n
903
Set OPERATION[n] := CONTINUE
Set PTR_INDEX[n]:=NEW_INDEX()
no
901
STATE[u]:=nil
Set E to set of edges with u for a tail.
Is E empty?
yes
902
Is u the terminal or throw vertex of the routine?
yes
no
no
904
Set e to any edge in E
Is e an exceptional edge?
no
905
Can edge e throw exception?
no
yes
yes
906
Add TAIL(e) to set NEED
907
Does e have form ``match T?'' for some T?
no
yes
909
Recursively invoke CLEANUP_TREE(HEAD(e))
908
Invoke CATCH_CHAIN(u)
912
Set n:= ALLOCATE(STATE[HEAD(e)])
Set OPERATION[n] := ~D(X)
Set STATE[u] := n.
OBJECT_INDEX[u]:=NEW_INDEX();
910
Does edge e have form ``~D(&X) for some D and X?
yes
no
911
Set STATE[u]:=STATE[HEAD(e)]
Remove e from E.
Is E the empty set?
no
913
end

FIG. 9


start CATCH_CHAIN(u)
Set list HANDLERS to empty.
Set w:=u
1000
1001
Is there an edge e of the form ``match T'' for some T and such that TAIL(e)=w?
no
1006
Invoke CLEANUP_TREE(w)
yes
1002
Set edge g to edge with form ``(true)'' such that TAIL(g)=HEAD(e).
Set n:= ALLOCATE (STATE[w])
STATE[u]:=n
Set OPERATION[n]:=TRY
Set CHAIN[n]:=HANDLERS
Set SETJMP_ INDEX[n]:=NEW_INDEX()
1007
Append CATCH(T,HEAD(g)) to list HANDLERS
1003
end
Set edge f to edge with form ``(false)'' such that TAIL(f)=HEAD(e).
1004
Set w:= HEAD(f)
1005

FIG. 10

FIG. 11







FIG. 12



FIG. 13


1401
(succeed)
T(&ant)
L1
1400
x>0?
CONTINUE
(true)
(false)
~T(&ant)
S(&cat)
1408
T(&dog)
TRY
~S(&elk)
S(&boa)
1409
(succeed)
1410
woof()
~S(&cat)
1411
(succeed)
S(&elk)
1412
1420
~T(&dog)
~T(&dog)
woof()
1413
(succeed)
(succeed)
1421
~S(&boa)
~S(&cat)
~S(&elk)
1406
~T(&ant)
(succeed)
L2
1426

FIG. 14


start
1500
Set all elements of T(u) to IDENTITY.
1501
Is u in set NEED?
no
yes
1503
1502
Set edge e to edge such that TAIL(e)=u
Set n:=STATE[HEAD(e)]
For each node m in the cleanup tree,
set T(u) [PTR_INDEX[m]]:=BOTTOM
1504
1505
T(u)[PTR_INDEX[n]]:=TOP
1506
CONTINUE
What is OPERATION[n]?
TRY
~D(&X)
T(u) [SETJMP_INDEX[n]]:=TOP
T(u)[OBJECT_INDEX[n]]:=TOP
1508
1507
1509
T(u)[KIND_INDEX[n]]:=TOP
yes
Set n:=PARENT[n]
Is n=nil?
no
1510
yes
end

FIG. 15


start
1600
Set all elements of DOWNSAFE(e) to IDENTITY.
1601
Does edge e have form ``(fail)''?
yes
1602
Set DOWNSAFE := T(HEAD(e))
1603
Invoke EFFECT(e,DOWNSAFE(e))
1604
Is e an exceptional edge?
no
yes
1605
Does there exist a normal edge f such that HEAD(e)= TAIL (f)
no
yes
1606
Set all elements of DOWNSAFE(e) to BOTTOM.
end

FIG. 16


start
1701
Set UPSAFE(e) := T(TAIL(e))
1708
1702
Does edge e have form ``(fail)''?
no
Invoke EFFECT(e,UPSAFE(e))
yes
1704
1703
Set k := 0
Is k<N_INDEX?
no
end
yes
1707
Set k := k+1
false
DOWNSAFE*(TAIL(e))[k]?
true
1705
Set UPSAFE(e)[k]:=TOP
1706

FIG. 17


start EFFECT(e,f)
Set N to set of nodes in cleanup tree that represent destructions of objects.
1800
1803
1801
Remove n from N
Is set N empty?
yes
end
no
Set n to any node in N.
1802
no
Is address of object corresponding to node n modified by an instruction on edge e?
1804
yes
Set f[OBJECT_INDEX[n]]:= BOTTOM;
1805

FIG. 18

FIG. 19


start
Set E to set of edges in control-flow graph.
1900
1903
Remove e from E
Is set E empty?
1901
no
Set e to any element of E.
1902
Set k:=0
1904
1906
Set k:=k+1
Is k<N_INDEX ?
1905
no
true
UPSAFE*(TAIL(e))(k)?
1907
false
true
DOWNSAFE*(TAIL(e))(k)?
1908
false
UPSAFE*(HEAD(e))(k)?
1909
false
1910
true
false
DOWNSAFE*(HEAD(e))(k)?
true
Invoke BIT_DIFFERENCE (k)
1911

FIG. 20


start BIT_DIFFERENCE(k)
2000
To which partial map does k belong?
OBJECT_INDEX[n]
OPERATION[n] is ~D(&X) for some X. Insert ``&REC(n).destructor.object = &X''
SETJMP_INDEX[n]
2002
Insert `` setjmp(&REC (n).try_block.buffer)''
PTR_INDEX[n]
Is OPERATION (n)=CONTINUE ?
2003
yes
no
2004
Insert ``EH_stack_ptr:=SAVER.next''
2005
Insert ``EH_stack_ptr :=&REC (n)''
KIND_INDEX[n]
2006
OPERATION[n] is TRY?
yes
Insert ``ITEM(n).tag := TRY''
2007
no
2009
Insert ``ITEM(n).tag := DESTROY''
2008
Insert ``&REC (n).try_block.catch_info = CATCH(n)''
2010
OPERATION[n] is ~D(&X) for some X. Insert ``&REC (n).destructor.dtor =&~D''
2011
Is PARENT[n] ≠nil ?
no
yes
2013
Insert ``REC(n).next = &REC(PARENT[n])''
Is OPERATION[PARENT[n]]=CONTINUE ?
no
2012
yes
yes
end
2014
Is n=SAVER ?
no
Insert ``REC (n).next = REC(SAVER).next''
2015

FIG. 21


start
2100
For each node n in cleanup tree such that OPERATION(n)≠CONTINUE, add declaration for REC(n) to routine.
2101
Is SAVER=nil ?
yes
end
no
2102
Insert ``REC(SAVER).next=EH_stack_ptr''

FIG. 22


2201
(succeed)
T(&ant)
L1
2200
x>0?
2203
(true)
(false)
ra.next =EH_stack_ptr;
2250
2253
ra.kind =DESTROY;
ra.destructor.dtor = & ~T
ra.destructor.object = &ant;
rt.kind =TRY;
rt.next=&ra;
rt.handlers = CHAIN(u)
rc.kind = DESTROY
rc.next = rt.next;
rc.destructor.dtor = & ~S;
rd.kind:=DESTROY;
rd.next=&rc;
rd.destructor.dtor = & ~T;
EH_stack_ptr = &rc;
setjmp(&rt.try_block.buffer)
2207
S(&cat)
2257
rc.destructor.object = &cat;
2208
T(&dog)
rd.destructor.object = &dog;
EH_stack_ptr = &rd;
2258
S(&boa)
2209
(succeed)
2210
2260
woof()
EH_stack_ptr = &rc;
2211
(succeed)
2212
2263
~T(&dog)
EH_stack_ptr = ra.next;
2213
(succeed)
2219
S(&elk)
re.kind = DESTROY
re.next = &ra;
re.destructor.dtor = & ~S;
re.object = &elk;
EH_stack_ptr = &re;
2269
2220
woof()
2221
~S(&boa)
~S(cat)
(succeed)
~S(&elk)
2222
2271
EH_stack_ptr = ra.next;
~T(&ant
L2
(succeed)

FIG. 23

```
struct EH_item ra, rb, rc, rd, re, rt;   2301
L1:
ra.next = EH_stack_ptr;   2303
T(&ant);
if( x>0 ) {
     S(&boa);
     ~S(&boa);
} else {
    ra.kind = DESTROY;
    ra.destructor.dtor = &~T;
    ra.destructor.object  = &ant;
    rt.kind = TRY;
    rt.next = &ra;
    rt.try_block.handlers = ...;
    rt.next = &ra;
    rc.kind = DESTROY;
    rc.destructor.dtor = &~S;
    rc.next = &rt;
    rd.kind = DESTROY;
    rd.destructor.dtor = &~T;
    rd.next = &rc;
    eh_stack_ptr = &rc;
    if( setjmp( &rt.try_block.buffer)==0 ) {
        S(&cat);
        rc.destructor.object  = &cat;
        T(&dog)
        rd.destructor.object  = &dog;
        eh_stack_ptr = &rd;
        woof();
        EH_stack_ptr = &rc;
        ~T(&dog);
        EH_stack_ptr = ra.next;
         ~S(&cat);
    } else {
    re.kind = DESTROY;
        re.next = &ra;
        re.destructor.dtor = &~S;
        eh_stack_ptr = &re;
        S(&elk);
        re.destructor.object  = &elk;
        woof();
        EH_stack_ptr = ra.next
        ~S(&elk);
    }
}
~T&ant)
L2:
```

FIG. 24

```
struct R {
   R(); ~2402
   ~R() throw();~2403
};
...
{
   i=0;
   do {~2408
      R fox;~2409
      woof();~2410
      i=i+1;
   } while( i<100 );~2412
}
```



FIG. 25

FIG. 26


true
likely
false


start
2700
Set all elements of $DOWNSAFE(e) to IDENTITY.
2701
Is edge e rarely taken?
yes
no
2702
Set $DOWNSAFE := to represent strict down-safety for e.
2703
Is tail of e the tail of some other edge that is rarely taken?
no
yes
2704
Set P to function that maps x to false if x=false, and ``likely'' otherwise.
2705
For each element f of $DOWNSAFE(e), set f:=Pof.
end

FIG. 27


start
Set $UPSAFE := to function of e that represents strict up-safety
2801
Is edge e rarely taken?
2802
no
yes
Set k := 0
2803
Is k<N_INDEX?
2804
no
end
yes
$DOWNSAFE*(TAIL(e))[k]?
2805
false
Set k := k+1
2807
true
likely
Set $UPSAFE(e)[k]:=$UPSAFE(e)oTOP
2806

FIG. 28

FIG. 29


start
$UPSAFE*(TAIL(e))(k)?
2900
true
false
$DOWNSAFE*(TAIL(e))(k)?
2901
true
likely
false
$UPSAFE*(HEAD(e))(k)?
2902
false
true
2903
$DOWNSAFE*(HEAD(e))(k)?
false
likely
true
2904
Insert guard
end
Insert on edge e the operation corresponding to k
2905


ABOVE
CONTINUE
ant
cat
dog
elk
try
ID
BELOW

FIG. 30